

PageStream™ 466 Plus Technical Specifications

Printing Method	LED Plus Imaging Electrophotography (two component system)
Toner System	Standard: one black developer unit Optional: MICR via Quick Change Developer Station
Fusing Method	Heat and Pressure
Print Quality	Standard: 240 and 300 dots per inch quality switchable Multiple Resolution Mode
Printing Speeds	Letter-sized, portrait, two-across (8.5 x 11 inches) – 466 ipm Letter-sized, landscape, one-across (8.5 x 11 inches) – 302 ipm Invoice, landscape, two-across (6 x 9 inches) – 854 ipm
Maximum Printable Area	Pinfed Paper: 17 inches Pinless Paper: 18 inches
Monthly Capacity	Up to 12 million images

Paper Input

Form Sizes	Width: 6.5" to 18" infinitely variable Length: 3" to 28" in 1/6" increments Length fold to fold: 6" to 14" for stacking purposes
Form Type	One part continuous form Plain white paper stock Color stock; Card stock, Recycled content paper Preprinted, Adhesive labels, Carbonless, Pressure seal, ID cards Perforated, Punched, or Drilled
Form Weight	18 - 40 lbs. Bond Basic Weight (17 x 22) Grammage 70 to 160 g/m ² ± 5% Other weights subject to evaluation
Paper Feed	Continuous forms, box, or roll feed

Paper Output

Capacity	Forms 6" to 14" can be stacked in Internal Stacker Maximum stack height: 17.7", equivalent to 3,300 pages at 18 lbs. bond paper Roll (unlimited)
Post-Print Handling	Automated Integrated Power Stacker Standard Océ® Certified Post-Processing devices (i.e. Automatic Stacker, Folder, Cutter, Job Separator, Rewinder, Color Imprinter)
Post-Print Attachments	Standard: ADI (Additional Device Interface) Optional: IPPI (Intelligent Post-Processing Interface) for online attachment to various post-processing equipment Océ® Verification Manager

Controller

Technology	SRA2 (Scaleable Raster Architecture)
System Attachments	Standard: Choose one of the following: S/370/390, Channel, ESCON, SCSI, IEEE 1284, TCP/IP (Ethernet) Optional: A second System Attachment

Page Description Languages	Standard: Choose two from the following: IPDS, Page Mode, Enhanced Mode, Compatibility Mode Printer Control Language (PCL) 5e Optional: Choose two additional Page Description Languages
Options	Xerox DJDE and Metacode, PostScript via Océ® PRISMA Print server solutions Océ® PRISMA server family Océ® Distribution Manager

Physical

Weight	2,514 lbs.
Dimensions	Height: 60.3" Width: 90.0" Depth: 37.0"
Power Requirements	Voltage: 208 V, 3-phase, 49 Amps Frequency: 60 Hz, +/-1 Hz Operating: 14.6kVA Standby: 2.4kVA
Customer Supplied	Russell Stoll In-line receptacle #7428/78 Or Russell Stoll wall receptacle #7324/78
Océ® Supplied	Power cable (4 wire –3 phase + ground) and Russell Stoll plugs #7328/78

Environmental

Optimum Operating Temperature Range	59° - 80°F
Optimum Operating Humidity Range	45% – 55%
Acoustic Noise	Operating: 67 db Standby: 61 db
Heat Dissipation	Operating: 42,990 BTU / hr Standby: 7,170 BTU / hr
Approved Standards	UL, FCC Class A